


VF VEDAÇÃO E FIXAÇÃO LTDA.
PINO GUIA ISO 8735 DIN 7979



D1		m6		6.00	8.00	10.00	12.00	16.00	20.00	25.00	30.00	40.00	50.00
D2		M4 x	M5 x	M6 x 1,00		M8 x	M10 x	M16 x	M20 x 2,50		M24 x		
Rosca		0,70	0,80			1,25	1,50	2,00			3,00		
A		0.80	1.00	1.20	1.60	2.00	2.50	3.00	4.00	5.00	6.30		
C		2.10	2.60	3.00	3.80	4.60	6.00		7.00	8.00	10.00		
T1		6.00	8.00	10.00	12.00	16.00	18.00	24.00	30.00		36.00		
Ref.													
L													
Nominal	Min.	Máx.											
16	15.50	16.50											
18	17.50	18.50											
20	19.50	20.50											
22	21.50	22.50											
24	23.50	24.50											
26	25.50	26.50											
28	27.50	28.50											
30	29.50	30.50											
32	31.50	32.50											
35	34.50	35.50											
40	39.50	40.50											
45	44.50	45.50											
50	49.50	50.50											
55	54.25	55.75											
60	59.25	60.75											
65	64.25	65.75											
70	69.25	70.75											
75	74.25	75.75											
80	79.25	80.75											
85	84.25	85.75											
90	89.25	90.75											
95	94.25	95.75											
100	99.50	100.75											
120	119.25	120.75											
140	139.25	140.75											
160	159.25	160.75											
180	179.25	180.75											
200	199.25	200.75											

Tolerância h8 e h11 sob consulta.